

# Product sheet



LINKEO LEGRAND

PDU, Zero-U, 1 phase 32A, 12 C13 outlets + 12 C19 outlets, with cord locking

REF. 646963 | EAN. 3414972471404

No price to display

> [Visit e-catalogue](#)

## Product characteristics

- 1 phase - 32A
- 12 C13 outlets + 12 C19 outlets, with cord locking system
- Max power 7,4kW
- Equipped with hydraulic magnetic circuit protection with high current interruption capacity.
- 3 m power supply cord with IEC 60309 32A plug

## Les + prod

### Installation

- Easy installation thanks to the 330° rotating cable input for a perfect orientation of the cable and no interference in the cabinet. Numbered outlets to ease the identification of each server. Supplied with 2 sets of metal fixings: button for screwless fixing, or standard screw-type brackets.

### Usage

- Each C13 and C19 outlets are numbered gradually from the input and equipped with cord locking system to avoid any accidental disconnection (100 Newton retention force)

### Advantages

- High ambient temperature rating: 60°C
- 330° rotative cable inlet
- Numbered outlets

## Documentation

### TECHNICAL DOCUMENTATION

-  [LE13706AC.pdf](#) | PDF (2.71Mo)
-  [FT-646963-EN-02.pdf](#) | PDF (1.56Mo)
-  [FT-646963-FR-02.pdf](#) | PDF (1.57Mo)
-  [User\\_Guide\\_Linkeo\\_DC\\_PDUs\\_4.0.34.pdf](#) | PDF (8.92Mo)
-  [User\\_Guide\\_LinkeoDC\\_PDUs\\_4.0.33.pdf](#) | PDF (8.73Mo)

### CATALOGUE PAGE & OTHERS

-  [ex223001\\_1039.pdf](#) | PDF (0.18Mo)

CAD & Design specs / BIM

- Basic PDU.rfa | RFA (4.21Mo)
- PDU basique.rfa | RFA (4.21Mo)

Software & configurators

-  PDU\_LDC\_040034-50319\_Firmware.bin | BIN (16.22Mo)
-  PDU\_LDC\_040034-50319\_ReleaseNotes.pdf | PDF (0.86Mo)
-  PDU\_LDC\_040033-49667\_Firmware.bin | BIN (16.21Mo)
-  PDU\_LDC\_040033-49667\_ReleaseNotes.pdf | PDF (0.85Mo)

Agreements & Certificates

-  Decl. UE RED-NN23O9J5 001 | (0.64Mo)
-  LGRP-01787-V01.01-FR.pdf | PDF (1.31Mo)
-  LGRP-01787-V01.01-EN.pdf | PDF (1.36Mo)