

Product data sheet

Specifications



Network Management Card, Network Management Cards, for Easy UPS 3 Series, 3-Phase, remotely monitor and manage the UPS

AP9547

Overview

Presentation	<p>The Network Management Card for Easy UPS 3 Series (AP9547) enables secure remote monitoring and control of one Easy UPS 3S, Easy UPS 3M or Easy UPS 3L through the easy-to-use web browser interface, via EcoStruxure™ IT Software or another SNMP-enabled system.</p> <p>A 12-month Secure NMC Subscription, that allows the customer to access future firmware updates, is included with the purchase of the card. Upon expiration of the provided Secure NMC Subscription the purchase of a new Secure NMC Subscription is required to access future firmware updates..</p>
--------------	---

Lead time	Usually in Stock
-----------	------------------

Main

Product or Component Type	Network Interface
Provided Equipment	User Manual USB cable

Physical

Height	1.7 in (4.4 cm)
Width	2.05 in (5.2 cm)
Depth	3.1 in (8.0 cm)
Net Weight	0.11 lb(US) (0.05 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Conformance

Standards	CISPR 32 EN 55024 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6 EN 61000-4-8 EN 61000-6-2 EN/IEC 62040-2
Product Certifications	FCC Class A ICES-003 VCCI Class A AS/NZS

Environmental

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature for Operation	23...113 °F (-5...45 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
Storage Relative Humidity	0...95 %

Communications & Management

Communication network type	10/100/1000BASE-T
----------------------------	-------------------

Ordering and shipping details

GTIN	731304422495
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 in (5.0 cm)
Package 1 Width	6.7 in (17.0 cm)
Package 1 Length	9.4 in (24 cm)
Package 1 Weight	10.6 oz (300 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	44
Package 2 Height	19.3 in (49 cm)
Package 2 Width	13.8 in (35 cm)
Package 2 Length	24.4 in (62 cm)
Package 2 Weight	33.25 lb(US) (15.08 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	352
Package 3 Height	45.2 in (114.9 cm)
Package 3 Width	38.2 in (97 cm)
Package 3 Length	38.2 in (97 cm)
Package 3 Weight	276.9 lb(US) (125.6 kg)

Sustainability



Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant with Exemptions

China Rohs Regulation

[China RoHS declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)