

Product data sheet

Specifications



Device monitoring and management, Network Management Cards, NMC4 for Galaxy VS, Galaxy VL & Galaxy VXL, secure remote UPS monitoring and management

AP9644

Overview

Presentation	Network Management Card for easy monitoring and managing of the Galaxy VS or Galaxy VL. The UPS status can be monitored and managed remotely through the UPS Web Interface, Modbus, or through EcoStruxure IT's cloud-enabled and on-premise software suites.
Lead time	Usually Ships within 2 Weeks

Main

Range of Product	Network Management Cards
Range Compatibility	Galaxy VS Galaxy VL Galaxy VXL
Product or Component Type	Device monitoring and management
Provided Equipment	Temperature Sensor Micro-USB cable Installation manual
Number of input phases	3
Standards	EN 55035 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6 EN 61000-4-8 EN 61000-4-11 EN 62040-2 EN 55011:A1 EN 55024:A1 EN 55032:class A VCCI class A ICES-003:issue 6

General

Variant option	Environmental monitoring with Modbus
----------------	--------------------------------------

Physical

Net Weight	0.31 lb(US) (0.14 kg)
Width	4.76 in (12.1 cm)
Height	1.50 in (3.8 cm)
Depth	4.25 in (10.8 cm)

Conformance

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product Certifications	FCC Class A AS/NZS
------------------------	-----------------------

Environmental

Storage Relative Humidity	0...95 %
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Ambient Air Temperature for Operation	23...113 °F (-5...45 °C)
Storage altitude	0.0000000000...49212.6 ft (0...15000 m) 0...50000 ft (0.0000000000...15240.0000000000 m)
Operating altitude	0...9842.52 ft (0...3000 m) 0...10000 ft

Communications & Management

Communication Network Type	10/100/1000BASE-T
Authentication	Radius
Communication Port Protocol	HTTP over secure sockets Layer (HTTPS) SSH FTP HTTP SNMP DHCP BOOTP (Bootstrap Protocol) TCP/IP

Ordering and shipping details

GTIN	731304355557
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.97 in (5.004 cm)
Package 1 Width	6.54 in (16.612 cm)
Package 1 Length	9.25 in (23.495 cm)
Package 1 Weight	1.759 lb(US) (0.798 kg)

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

How this information helps you >

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle)	181
--	-----

Environmental Disclosure	Product Environmental Profile
--------------------------	---

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
--	----

Packaging without single use plastic	No
--------------------------------------	----

EU RoHS Directive	Compliant with Exemptions
-------------------	---------------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

China RoHS Regulation	China RoHS declaration
-----------------------	--

Use Again

Repack and remanufacture

Circularity Profile	End of Life Information
---------------------	---

Removable battery	Yes
-------------------	-----

WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Take-back

No