





# APC Easy UPS BVX 700VA, 230V, AVR, USB Charging, Schuko Sockets

BVX700LUI-GR

#### **Overview**

Lead time Usually in Stock

#### Main

Main Input Voltage	230 V AC 1 phase
Main Output Voltage	230 V AC 1 phase
Rated power in W	360 W
Rated power in VA	700 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	Schuko
output connection type	2 Schuko
Cable length	1.2 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	User manual

#### **Batteries & Runtime**

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery voltage	12 V
Battery capacity	7.0 Ah
Battery life	23 year(s)
Replacement battery	APCRBC110 ☐
Extended runtime	0

#### **General**

Max runtime	120 min
Number of power module free slots	0
Number of power module filled slots	0

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Redundant	No
UPS size	WS

# **Physical**

Colour	Black
Height	13.8 cm
Width	9.8 cm
Depth	31 cm
Net weight	4.2 kg
mounting support	Floor
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

# Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	170280 V 230 V AC
cos phi	0.51

# Output

Maximum configurable power in W	360 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:00:01 360 W
Graph display	1
Half load runtime	00:06:00 180 W
Maximum configurable power in VA	700 VA
Transfer time	6 ms typical : 10 ms maximum

## Conformance

Product certifications	CE CB
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Equipment protection policy	Lifetime: 50000 euros

## **Environmental**

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	03000 m

Ambient air temperature for storage	-1540 °C
Storage Relative Humidity	095 % non-condensing
Storage altitude	03000 m
acoustic level	40 dBA
IP degree of protection	IP20

# **Surge Protection and Filtering**

Surge energy rate 273 J

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.2 cm
Package 1 Width	34.6 cm
Package 1 Length	14.2 cm
Package 1 Weight	4.5 kg
SCC14	10731304417634

## **Contractual warranty**

Warranty 2 years repair or replace



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information
Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information