

A solid red horizontal bar with rounded ends on the right side, containing the product code "DS-PDEBP2-EG2-WB" in white, uppercase, sans-serif font.

- Accidental press protection
- Fully remote configurable through App
- IP66 daily environment protection
- Frequency hopping against jamming for reliable transmission
- Optional lanyard and wristband accessory available

▪ Specification

Feature	
Button	2
Tamper Protection	None
Signal Strength Indicator	Support
Interface	
LED Indicator	Red / Green
Transmission	
Transmission Technology	Tri-X Wireless
Transmission Method	Two-Way RF Wireless
Transmission Frequency	433MHz
Transmission Security	AES-128 Encryption
Transmission Range(Free Space)	800m
Frequency Hopping	Support
Enrolling Method	Power up,Remote ID,QR Code
Electrical Characteristics	
Standard Battery Life	Up to 3 years (standby time)
Power Supply	Battery Powered
Battery Type	CR2035 x 1
Typical Voltage	3V
General	
Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Operation Humidity	10% to 90%
IP Rate	IP66
Dimension(WxHxD)	φ38 × 12mm
Weight	13.5g
Application Scenario	Portable

▪ Available Model

DS-PDEBP2-EG2-WB

▪ Accessory

▪ Optional

DS-PDB-IN-Wristband Emergency Button Wristband Accessory



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

