

Product datasheet

Specifications



Battery Breaker Kit, 630A, one circuit breaker for Easy UPS 3M/3L

E3MBBK100K200H

Overview

Presentation	Battery breaker kit that controls DC voltage sent from third party battery solutions to the UPS.
Lead time	Usually Ships within 6 Weeks

Main

Product or component type	Kit
Battery type	VRLA
Provided equipment	Installation guide

Batteries & Runtime

Number of battery free slots	0
Number of battery filled slots	0
Device mounting	Enclosed battery cabinet
battery power in VAh	0 VAh

Physical

Height	53 cm
Width	32 cm
Depth	23 cm
Net weight	13 kg
Mounting mode	Not rack-mountable

Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...4921 ft
Relative humidity	0...95 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	80 cm
Package 1 Width	57 cm
Package 1 Length	50 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Weight	29 kg
------------------	-------


Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
REACH Regulation	REACH Declaration
China RoHS Regulation	China RoHS declaration