

MAXPRO® SERIES WORKSTATIONS

Enterprise Class Video Management Client System

Honeywell's MAXPRO® NVR (Network Video Recorder) and MAXPRO® VMS (Video Management System) are an industry-leading enterprise class digital CCTV solution.

The MAXPRO® VMS & NVR are built upon the best-in-class components and provide the flexibility and scalability to design a video system suited to a variety of end user applications. Honeywell is a total solution provider and offers all the components of a reliable and powerful video system including cameras, encoders, management software, servers, workstations, and video storage.

MAXPRO® Series workstations are the front-end of the MAXPRO® system, delivering live and recorded video and Graphical User Interface. The workstations are pre-loaded with the latest MAXPRO® software and are optimized for use, delivering crisp clear video images.

The MAXPRO® workstations leverage industry-leading IT components and are tested to the rigorous demands of a video system. The number of workstations within the MAXPRO® system is scalable to meet any application. The workstations are powered by industry-leading Intel processors.

MARKET OPPORTUNITIES

MAXPRO® Series workstations are a necessary component of the MAXPRO® video management system. The small form factor, high performance, and reliability of the server makes it an ideal solution where digital video is mission critical in application such as airports, and critical infrastructure operations.

FEATURES AND BENEFITS

- Capable of simultaneous record, playback, live view, archive, or transmission of digital video
- Utilizes Intel processor technology
- Video graphics card for smoother video integrations
- 16 GB of DDR4 RAM
- 256GB PCIe NVMe Class 35 M.2 SSD
- Available in tower configuration



SPECIFICATIONS		
DESKTOP		
OPERATIONAL	Operating System	Windows 10 IoT Enterprise
	Processor	Intel® Core™ i7 12700
	Memory	16GB DDR5
	Hard Drive	256GB PCIe NVMe Class 35 M.2 SSD
	Optical Drive	8x DVD RW 9.5mm
	Video Card	Nvidia T1000 8GB, 4 mDP to DP adapter
PANEL CONNECTIONS	USB	2x USB 3.2 Type-A Gen 1 (5GB) port 1x USB 3.2 Type-C Gen 2 (10GB) port 1x USB 3.2 Type-C Gen 2x2 (20GB) port with PowerShare
	Monitor Output	2 x DisplayPort, 4 x Mini DisplayPort
	Ethernet Port	1 x RJ-45 (1 Gigabit)
	Audio	1 x 1/8" Audio combo jack 1 x 1/8" Microphone In 1 x 1/8" Audio Line Out
ELECTRICAL	Input Voltage	100~240 VAC 50/60 Hz
	Power Consumption	500 Watt
MECHANICAL	Dimensions (W x H x D)	H: 14.68in, W: 6.81 in, D: 16.54 in (372.90mmx 173.00mmx420.20mm)
	Weight	18.739 lbs (8.5kg)
	Construction	Housing: Black
ENVIRONMENTAL	Temperature (Operating)	10°C (50°F) ~ 35°C (95°F)
	Relative Humidity (Operating)	20% to 85% (non-condensing) (non-condensing, Max dew point temperature = 26°C)
WARRANTY	Warranty and Support	5 years and Next Day Business Support

NOTE: Honeywell reserves the right, without notification, to make changes in product design or specifications.

ORDERING	
HMW8T	Honeywell MAXPRO® Workstation, Tower

For more information

buildings.honeywell.com/security

Honeywell Commercial Security

Emaar Business Park, Sheikh Zayed Road
Building No. 2, 2nd floor, 201
Post Office Box 232362
Dubai, United Arab Emirates
Tel: +971 4 450 5800
www.honeywell.com

HBT-SEC-HMW8T-01-ME(0523)DS
© 2023 Honeywell International Inc.

THE
FUTURE
IS
WHAT
WE
MAKE IT

Honeywell