Cisco public

CISCO
The bridge to possible

Cisco Webex

Webex Room Kit Plus

Contents

| Product overview | 3 |
|--|----|
| Product features and benefits | 4 |
| Webex Room Kit Plus prominent features and differentiators | 5 |
| An affordable way to purchase hardware | 6 |
| Product specifications | 6 |
| Ordering information | 11 |
| Warranty information | 13 |
| Cisco environmental sustainability | 13 |
| Cisco Services and Support | 13 |
| Cisco Capital | 14 |
| For more information | 14 |



Webex Room Kit Plus is a powerful collaboration solution that integrates with flat-panel displays to bring more intelligence and usability to your medium to large-sized meeting rooms - whether registered on the premises or to Webex in the cloud.

Product overview

Webex[™] Room Kit Plus delivers the unmatched video and audio experience customers have come to expect from Cisco. In addition, new capabilities enable even smarter meetings, smarter presentation capabilities, and smarter room and device integrations – further removing the barriers to usage and deployment of video in medium to large-sized rooms.

The Room Kit Plus – comprising a powerful codec, a quad-camera bar with integrated speakers and microphones* and the intelligent Room Navigator control panel – is ideal for rooms that seat up to 14 people. It offers sophisticated camera technologies that bring speaker-tracking and auto-framing capabilities to medium to large-sized rooms. The product is rich in functionality and experience but is priced and designed to be easily scalable to all of your conference rooms and spaces – whether registered on the premises or to the Webex cloud service.

^{*} Integrated microphones for speaker tracking only



Figure 1. Webex Room Kit Plus in a conference room

Product features and benefits

| Feature | Benefit |
|---------------------|--|
| Smart meetings | Brings intelligent views to medium to large-sized rooms with discreet, integrated cameras Best overview: Automatically detects meeting participants and provides ideal framing Speaker tracking: Detects and switches between active speakers and provides ideal framing Great audio experience with integrated speakers Automatic noise suppression reduces disruptive sounds coming from the meeting room (e.g., typing, paper rustling) Simplified meeting-join experience with One Button To Push (OBTP) for scheduled devices in Webex meetings, whether registered on-prem or to the Webex cloud service Automatic wake-up: System "wakes up" when someone walks into the room, and recognizes them through their mobile device Easily controlled by the Webex Room Navigator control unit or with the Webex App End-to-end security |
| Smart presentations | Supports dual screens for video and content Supports dual content sources for local meetings View whiteboard content and annotations shared from Webex Board, Webex Desk Pro, or the Webex App; participate in whiteboarding sessions through the Webex App 4K content sharing (local 30 fps; remote 5 fps) Wired or wireless content sharing |

| Feature | Benefit |
|------------------------------|--|
| Smart integrations | Metrics: Counts people in the room, enabling analytics for better resource planning Automatic screen/display integration through HDMI CEC Supports Wi-Fi Control system integration: Control peripherals such as lights and blinds through the Webex Room Navigator |
| Built for cloud and premises | Flexibility to register on the premises or to the cloud through Webex Hardware is optimized to run on a cloud platform, for great experiences in shared rooms and spaces with easy access to hosted conferences |



Figure 2.Default components of the Webex Room Kit Plus: Webex Codec Plus, Webex Quad Camera, Webex Room Navigator

Webex Room Kit Plus prominent features and differentiators

Bringing more intelligence to medium to large-sized rooms

The Webex Room Kit Plus is video innovation in a box, bringing more intelligence and usability to your medium to large-sized rooms team collaboration rooms. While others are still struggling to insert advanced features such as speaker tracking, wireless sharing, and 4K content into their high-end products, Webex by Cisco is already proliferating these innovations to meeting rooms of all sizes in a cost-effective and simple way. With the Room Kit Plus, Webex is helping customers experience smarter meetings, enable smarter presentations, and create smarter room and device integrations. These features were previously the domain of higher-end video conferencing rooms, but can now be brought to every room and every team. And when registered to Webex, additional cloud-based functionalities are enabled that enhance the user experience and team workflow as well as further simplifying deployment.

- **Smart meetings:** Powerful, integrated cameras deliver intelligent view capabilities, such as automatic framing and speaker tracking; automatic noise suppression reduces meeting disruptions
- Smart presentations: Dual screens, dual content sources, wireless sharing, and 4K content make for great presentations
- **Smart rooms:** People count for usage metrics and resource allocation; tight integrations with screens to enhance user interactions; APIs and macros allow meeting personalization
- Audio-visual integration: The Codec Plus is an entry-level integrator codec, supporting third-party audio systems. Control systems can use RS-232 with a USB adapter, or SSH.
- Registration flexibility: Built for both cloud and on-premises deployment, protecting your investment



Figure 3. Webex Room Kit Plus in a large meeting room

An affordable way to purchase hardware

Webex Hardware as a Service provides a new way to purchase hardware with a simple, scalable and flexible way to pay. Stay up to date with the latest models of IP Phones and Webex Devices to enhance collaboration and create workspaces for the future. And get ready for all the power of Cisco's unified cloud platform!

<u>Learn more about Webex Hardware as a Service and the devices available</u>. <u>Click here</u> to access the Webex Hardware as a Service data sheet.

Product specifications

Table 1. Specifications

| Specification | Description |
|---|--|
| Software compatibility | Cisco Collaboration Endpoint Software Version 9.14.5 or later, or Webex RoomOS |
| Default components in Webex Room Kit Plus | Webex Codec Plus Webex Quad Camera Webex Room Navigator control unit Wall mount for Quad Camera |
| Available integrator bundles | Webex Room Kit Plus PTZ 4K (featuring the Webex PTZ 4K Camera) |
| Optional hardware components | Cisco Table Microphone, Cisco Ceiling Microphone, Wall mount for Codec Plus, cables, spare Webex PTZ 4K Camera, spare Webex Precision 60 Camera, spare Cisco TelePresence SpeakerTrack 60 Camera |
| Bandwidth | Up to 6 Mbps point-to-point |
| Minimum bandwidth for | H.264 |

| Specification | Description | |
|--|---|--|
| resolution/frame rate | 720p30 from 768 kbps 720p60 from 1152 kbps 1080p30 from 1472 kbps 1080p60 from 2560 kbps | |
| Firewall traversal | Cisco Expressway[™] technology H.460.18, H.460.19 firewall traversal | |
| Video standards | H.264, H.265, and H.263 for TANDBERG[™] MXP interoperability only | |
| Video inputs | One HDMI input supports formats up to maximum 1080p60 Two HDMI inputs support formats up to maximum 4K (3840 x 2160) at 30 fps including HD1080p60 Extended Display Identification Data (EDID) Consumer Electronics Control (CEC) 2.0 | |
| Video outputs | Two HDMI outputs support formats up to 3840 x 2160p60 (4Kp60) Consumer Electronics Control (CEC) 2.0 | |
| Encode and decode | Main video: Full HD 1080p60 Presentation channel: UHD 4K 2160p5, including 1080p30 and 720p60 | |
| Audio standards | • G.711, G.722, G.722.1, G.729, AAC-LD, and Opus | |
| Audio features | High-quality 20 kHz audio Subwoofer line out for Quad Camera Prepared for inductive loop (line out) Automatic Gain Control (AGC) Automatic noise reduction Active lip synchronization | |
| Audio inputs | Three microphones, 4-pin mini-jack Embedded audio on two HDMI inputs Bluetooth® - Not available on Non Radio Version* | |
| Audio outputs | 1 line out mini-jack (stereo) (Codec Plus) 1 RCA output for subwoofer (Quad Camera) Embedded audio on one HDMI output HDMI input #1 supports Audio Return Channel (ARC): Audio output to Quad Camera Bluetooth® - Not available on Non Radio Version* | |
| Speakers (Quad Camera) | High-quality speakers Frequency response: 70 Hz to 20 kHz Max output level SPL 90dB | |
| Speaker tracking (Quad Camera, SpeakerTrack 60) | 6-element microphone array for accurate speaker tracking Quad Camera can support group framing feature with 5x zoom capability SpeakerTrack 60 can support close-up feature with 20x zoom capability | |
| PresenterTrack (available when pairing with PTZ 4K Camera, Precision 60 Camera) | Al-powered face and upper body detection capability Camera automatically follows the active presenter within a defined zone and helps ensure optimized view | |

| Specification | Description |
|---|--|
| Dual stream | H.239 (H.323) dual stream Binary Floor Control Protocol (BFCP) (SIP) dual stream Support resolutions up to 3840 x 2160p5 (4Kp5),1080p30 and 720p60 |
| Wireless sharing | Webex App (up to 3840 x 2160p5) Cisco Intelligent Proximity client (up to 1920 x 1080p5) Miracast (1080p30) - Not available on Non radio version* |
| MultiSite features (embedded multipoint) (optional upgrade) | Adaptive SIP/H.323 MultiSite 3-way resolution up to 1080p30 + content up to 4Kp5 4-way resolution up to 720p30 + content up to 4Kp5 Full individual audio and video transcoding H.323/SIP/VoIP in the same conference Support for presentation (H.239/BFCP) from any participant at resolutions up to 3840 x 2160p5 Best Impression (automatic continuous presence layouts) Encryption and dual stream from any site |
| Protocols | H.323 SIP Webex ISDN PRI/BRI using the optional ISDN Link |
| Embedded encryption | H.323 and SIP point-to-point Standards-based: H.235 v3 and Advanced Encryption Standard (AES) Automatic key generation and exchange |
| IP network features | DNS lookup for service configuration Differentiated services (Quality of Service [QoS]) IP-adaptive bandwidth management (including flow control) Automatic gatekeeper discovery Dynamic playout and lip-sync buffering H.245 Dual-Tone Multi-Frequency (DTMF) tones in H.323 RFC 4733 DTMF tones in SIP Date and time support using Network Time Protocol (NTP) Uniform Resource Identifier (URI) dialing Dynamic Host Configuration Protocol (DHCP) 802.1X network authentication 802.1Q Virtual LAN 802.1p [QoS and Class of Service (CoS)] Cisco Media Assure and ClearPath, including packet loss-based downspeeding |
| Call control | Cisco Unified Communications Manager (CUCM) Native registration CUCM Requires CUCM Version 10.5.2 or later with device pack Room Kit Plus Cisco Expressway Native registration with Expressway Webex Third-party H.323 Gatekeepers and standards-based SIP proxies |

| Specification | Description |
|------------------------------------|--|
| IPv6 network support | Single call stack support for both H.323 and SIP Dual-stack IPv4 and IPv6 for DHCP, SSH, HTTP, HTTPS, DNS, DiffServ Support for both static and automatic IP configuration (stateless address auto configuration) |
| Security features | Management using HTTPS and SSH IP administration password Password to access administration features on Webex Room Navigator controller Disable IP services Network settings protection |
| Certificate management | Certificate Authority Proxy Function (CAPF) support for additional security Manufacturer-Installed Certificates (MIC) Locally Significant Certificates (LSC) X.509 Digital Certificates (DER encoded binary); both DER and Base-64 formats are acceptable for the client and server certificates; certificates with a key size of 1024, 2048, and 4096 are supported |
| Other interfaces | USB 2.0 port, mini USB port, factory reset pinhole |
| Network interfaces Codec Plus | 1 Ethernet (RJ-45) 10/100/1000 for LAN 1 Ethernet (RJ-45) 10/100/1000 for direct pairing with camera (camera control) 1 Ethernet (RJ-45) 10/100/1000 with PoE, for direct pairing with Webex Room Navigator Wi-Fi 802.11a/b/g/n/ac 2.4 GHz and 5 GHz for LAN- not available in non-radio versions 2x2 multiple input and multiple output (MIMO) Note: Due to compliance regulations, it is required that 802.11d is enabled in the access point for the product to operate properly within 5725 MHz - 5875 MHz. Using a Wifi connection is a flexible option, however an Ethernet connection is always preferred for high performance. |
| Power supplies (2) | 100 to 240 VAC, 50/60 Hz, 12V DC input Average 20 W, peak 70W Quad camera must be used with power supply FSP FSP070-AHAN2 or AcBel ADF019 |
| Operating temperature and humidity | 0°C to 35°C (32°F to 95°F) ambient temperature 10% to 90% Relative Humidity (RH) |
| Storage and transport temperature | • -20°C to 60°C (-4°F to 140°F) at RH 10% to 90% (noncondensing) |
| Locking mechanism | Kensington security lock |

Specification Description Dimensions 000.0 • Quad Camera: Width: 37.4 in. (95.0 cm) Height: 4.7 in. (12.0 cm) Depth: 4.0 in. (10.3 cm) Weight: 10.6 lb. (4.8 kg) • Codec Plus: Width: 14.1 in. (35.9 cm) Height: 1.7 in. (4.3 cm) Depth: 5.6 in. (14.3 cm) Weight: 3.9 lb. (1.77 kg) • (4) 5K CMOS sensors with machine intelligent switching; providing single HD output at 1080p **Camera overview** (Quad Camera) • Support up to 60 fps • 15.1 MP image sensor • 1/1.7 CMOS • 5x digital zoom (3 tele-lenses each with 50° horizontal field of view) • f/2.0 aperture • 83° horizontal field of view; 51.5° vertical field of view • Auto-framing (audio + face detect) • 5120 x 2880 pixel resolution • Auto focus, brightness, and white balance • Focus distance 1 m to infinity • 1920 x 1080 at 60 frames per second (fps) Camera overview (SpeakerTrack 60) • 10x optical zoom, 2x digital zoom, 20x zoom combined • Pan range: +/-100 degrees, Tilt range: +/-20 degrees, Tracking horizontal FoV: 80 degrees • Focus distance 1.0m to infinity (wide) • F-value 1.5 • Manual or automatic to do focus, white balance, and brightness

| Specification | Description |
|-------------------------------------|--|
| Standards and Regulatory Compliance | Regulatory compliance Directive 2014/35/EU (Low-Voltage Directive) Directive 2014/30/EU (EMC Directive) - Class A Directive 2014/53/EU (Radio Equipment Directive) Directive 2011/65/EU (RoHS) Directive 2002/96/EC (WEEE) NRTL approved (Product Safety) FCC CFR 47 Part 15B (EMC) - Class A Please check the Product Approval Status Database at https://www.ciscofax.com/ for approval documents per country. |

^{*}The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Cisco Systems, Inc. is under license. Other trademarks and trade names are those of their respective owners.

Ordering information

To place an order, please contact your local Cisco representative and refer to Table 2.

 Table 2.
 Ordering information

| Product Name | Part Number | Compliance Model Number |
|---|--|-------------------------------|
| Webex Room Kit Plus - Subscription pricing (MSRP') • Webex Codec Plus • Webex Quad Camera • Webex Room Navigator Control Unit • Webex Service | CS-KITPLUS-MSRP-K9 CS-CODEC-PLUS+ CS-QUADCAM+ CS-T10-TS+ A-SPK-SH-RMK (A-SPK-SH) | TTC7-25 TTC8-10 TTC5-15 |
| Webex Room Kit Plus (GPL**) • Webex Codec Plus • Webex Quad Camera • Webex Room Navigator Control Unit | CS-KITPLUS-K9 CS-CODEC-PLUS+ CS-QUADCAM+ CS-T10-TS+ | TTC7-25 TTC8-10 TTC5-15 |
| Webex Room Kit Plus - NO RADIO • Webex Codec Plus - NO RADIO • Webex Quad Camera • Webex Room Navigator Control Unit | CS-KITPLUS-NR-K9 CS-CODEC-PLUS-NR+ CS-QUADCAM+ CS-T10-TS+ | TTC7-25 TTC8-10 TTC5-15 |
| Webex Room Kit Plus - NO CRYPTO • Webex Codec Plus • Webex Quad Camera • Webex Room Navigator Control Unit | CS-KITPLUS-K7 CS-CODEC-PL-NR-K7+ CS-QUADCAM+ CS-T10-TS+ | TTC7-25 TTC8-10 TTC5-15 |

| Product Name | Part Number | Compliance Model Number |
|---|---|--|
| Webex Room Kit Plus - TAA compliant • Webex Codec Plus - TAA, NO RADIO, or • Webex Codec Plus - TAA • Webex Quad Camera • Webex Room Navigator Control Unit | CS-KITPLUS-K9++ CS-CODEC-PLUS-NR++ CS-CODEC-PLUS++ CS-QUADCAM+ CS-T10-TS+ | TTC7-25 TTC7-25 TTC8-10 TTC5-15 |
| Options | | |
| Cisco Table Microphone with 3.5mm plug | CS-MIC-TABLE-J= | |
| Extension cable for Table Microphone | CAB-MIC-EXT-J= | |
| Cisco Ceiling Microphone | CTS-MIC-CLNG-G2 | |
| Shielded cable for Ceiling Mic (non-plenum rated) | CAB-ETHRSHLD-10M | |
| Wall Mount Kit for Codec Medium | CS-KITPLUS-WMK | |
| 8 m HDMI 2.0 certified cable | CAB-PRES-2HDMI-GR | |
| HDMI 2.0 cable 1.5 m/5 ft, gray | CAB-2HDMI-1.5M-GR | |
| HDMI 2.0 cable 3 m/10 ft, gray | CAB-2HDMI-3M-GR | |
| Ethernet cable 1.5 m/5 ft, gray | CAB-ETH-1.5M-GR | |
| Ethernet cable 3 m/10 ft, gray | CAB-ETH-3M-GR | |
| Ethernet cable 5 m/16.4 ft, gray | CAB-ETH-5M-GR | |
| Software options - ordered separately | | |
| Remote Monitoring | L-ROOM-RM (L-TP-RM) | |
| MultiSite (embedded multipoint) | L-KITPLUS-MS (L-ROOM-PAK) | |
| Spares | | |
| Webex Codec Plus | CS-CODEC-PLUS= | TTC7-25 |
| Webex Codec Plus - no radio, no crypto | CS-CODEC-PL-NR-K7= | TTC7-25 |
| Webex Codec Plus - no radio | CS-CODEC-PLUS-NR= | TTC7-25 |
| Webex Quad Camera | CS-QUADCAM= | TTC8-10 |
| Webex PTZ 4K Camera | CS-CAM-PTZ4K= | EVI-X200C |

| Product Name | Part Number | Compliance Model Number |
|---------------------------|-------------------|-------------------------|
| Webex Precision 60 Camera | CTS-CAM-P60= | TTC8-07 |
| Power supply 12VDC 70W | PSU-12VDC-70W-GR= | |

^{*} MSRP = Manufacturer's Suggested Retail Price

Warranty information

Webex Room Kit Plus has a 90-day limited liability warranty.

Cisco environmental sustainability

Information about Cisco's environmental sustainability policies and initiatives for our products, solutions, operations, and extended operations or supply chain is provided in the "Environment Sustainability" section of Cisco's <u>Corporate Social Responsibility</u> (CSR) Report.

Reference links to information about key environmental sustainability topics (mentioned in the "Environment Sustainability" section of the CSR Report) are provided in the following table:

| Sustainability topic | Reference |
|--|------------------|
| Information on product material content laws and regulations | <u>Materials</u> |
| Information on electronic waste laws and regulations, including products, batteries, and packaging | WEEE compliance |

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

Cisco Services and Support

Cisco and our partners provide a broad portfolio of smart, personalized services and support that can help you realize the full business value of your Cisco collaboration investment by increasing business agility and network availability. This portfolio of services accelerates business innovation by harnessing the network as a powerful business platform. For more information about these services, please visit: https://www.cisco.com/go/collaborationservices.

^{**} GPL = Global Price List

Cisco Capital

Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. Learn more.

For more information

- · Learn more about Webex Room Kit Plus.
- Learn more about Webex Room Kit Plus PTZ 4K Integrator Bundle.
- Learn more about Webex Room Kit Plus Precision 60 Integrator Bundle.
- Download the Webex App.

Americas Headquarters Cisco Systems, Inc. San Jose, CA Asia Pacific Headquarters Cisco Systems (USA) Pte. Ltd. Singapore **Europe Headquarters**Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at https://www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: https://www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Printed in USA C78-738752-10 05/22