

DS-1LH1SCA3C-090B Coaxial Cable with power cable

Features and Functions

- 90m mini RG59 coaxial cable with power cable
- Conductor material of Coaxial cable is Bare copper
- Braiding material of Coaxial cable is Copper clad aluminum magnesium
- Conductor material of power cable is Bare copper
- Excellent anti-interference performance
- Excellent anti-aging performance



Specifications

Model		DS-1LH1SCA3C-090B
Coaxial Cable		
Conductor	Material	Bare copper
	Wire Gauge	26AWG
	Diameter	0.41±0.01mm
Insulation	Material	FPE
	Diameter	2.0±0.1mm
Tape	Material	Copper foil
Braid	Material	Copper clad aluminum magnesium
	Braiding Standard	5*16*0.12mm ±0.008mm
	Braiding Density	≥80%
Jacket	Material	PVC
Impedance		75ohms
Power Cable		
Conductor	Material	Bare copper
	Quantity	3
	Diameter	11*0.16±0.008mm
Insulation	Material	SR-PVC
	Diameter	1.2±0.1mm
Jacket	Material	PVC
General		
Length		90m
Color		Black

Distributed by

Available Model

DS-1LH1SCA3C-090B

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Europe
T +31-23-5542770
saleseuro@hikvision.com

Hikvision France
T +33(0)1-85-330-444
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +44-1628-9021-4
support.uk@hikvision.com