

## DS-K1802

### Value 1802 Card Reader (EM & MF & Keyboard)



- M1/ EM card reader
- PC+ABS material shell
- Built-in audible beeper
- Wiegand interface
- IP65

## ▪ Specification



Authentication	
Card reading frequency	13.56MHz/125KHz
General	
Power supply	12 VDC
Power consumption	≤ 1.6 W
Working temperature	-20 °C to 65 °C (-4 °F to 149 °F)
Working humidity	10% to 90% (no condensing)
Dimensions	115.9 mm × 43.3 mm × 17 mm (4.56"×1.70"×0.67")
Installation	Wall mounting with screws; Do not support gang box
Weight	Gross weight: 0.217 kg (0.48 lb) Net weight: 0.12 kg (0.26 lb)
Keypad	DS-K1802E/DS-K1802M: No keypad DS-K1802EK/DS-K1802MK: Keypad with 12 keys (0 to 9, *, #)
Buzzer	Support

## ▪ Available Model

DS-K1802E

## ▪ Accessory

### ▪ Optional

DS-K2801 Value Series Card Access Controller	ACT-C101#RUBB Value Series Card Access Controller
	

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

