

Description

Finosel[®], FS Universal Server Rack is compatible with a variety of servers and rackmountable networking equipment's with a Wide range of accessories such as fan, Wheel, Castor etc are preconfigured with all standing cabinets which makes it cost effective and impressive.



Applications

- ✓ Broadband, enterprise networking and data center applications
- ✓ Data and telecommunication devices and their distribution systems.
- ✓ High-density server and IT networking environments.
- ✓ Premise installations.
- ✓ Local area networks (LAN).

Standards & Features

- ✓ Excellent and elegant exterior design, sleek appearance, strong frame structure
- ✓ Adjustable feet and castors are available, moving conveniently and fixing reliable.
- ✓ Tempered glass front door with high density ring hole decoration and rear door with square holes.
- ✓ Massive front to rear ventilation capacity Up to 65+% with MD perforated front door.
- ✓ Cabinet size ranges from 18U to 47U in height
- ✓ Earthing grounding Kit
- ✓ Accommodates all standard 19-inch rackmount equipment & Compatible vertical PDUs/cable managers.
- ✓ Front and rear sets of equipment mounting rails adjustable.
- ✓ Split rear door design reduces closer to a wall clearance
- ✓ Leveling feet extend to allow enclosure to be positioned on uneven floors.
- ✓ Open top and bottom for cable access
- ✓ FS Cabinet are Flat pack design, 1763 lbs (800 kg)
- ✓ Optional MD perforated V Slot front door
- ✓ Lead-free & RoHS2 compliant.
- ✓ IP Degree Rating: IP 20
- ✓ Compatible with 19" International Standard, Metric System and ETSI Standard
- ✓ Comply with ANSI/EIA; RS-310-D; DIN41491:PART1; IEC297-2; DIN41494;PART1; GB/T3047.2-92 Standard

Roof Mount 4 Inch Fans

Rated Power	20W±10%
Rated Voltage	220 V
Rated Current	0.14A±10%
Frequency	50/60 Hz

Optional Front Door

MDB22-8HS	Honey Comb Front Door, 22U V Slote Design, 800mm Width, Black
-----------	---

Specification

Color	RAL9004 (Black)
Material & Thickness	SPCC cold rolled steel; Thickness : Mounting Profile : 2.00mm, Mounting angle :1.5mm; others: 1.2mm
Surface Finish	Degreasing, Pickling, Phosphoric, Cleaning, Powder coated
Loading Capacity	FS Static Loading: 1764 lbs (800 kg)

Name	Qty	Unit	Materials
Frame	2	Set	SPCC T= 2.00 mm
Single section glass front door with ring hole with Decorative Strip	1	Pcs	SPCC T= 1.20 mm
M12 Support feet	4	Pcs	SPCC T= 1.50 mm
Mounting angle < 37U	4	Pcs	SPCC T= 1.50 mm
Mounting angle > 37U	6	Pcs	SPCC T= 1.50 mm
2 inch Castor	4	Pcs	-----
Single section flat rear door with square hole (< W 600 x D 800)	1	Set	SPCC T= 1.20 mm
Split rear door with square hole from (> 800 depth)	1	Set	SPCC T= 1.20 mm
Top cover	1	Pcs	SPCC T= 1.20 mm
Bottom cover	1	Pcs	SPCC T= 1.20 mm
Fan Tray	1	Pcs	SPCC T= 1.20 mm
4 inch Axial Fan with UK style plug	4	Pcs	-----
Cable management (for 800mm width)	2	Pcs	SPCC T= 1.20 mm
M6 Square screws and nuts (Cage nut)	25	Pcs	-----

Side panel with quick open latch	4	Pcs	-----
Side panel with Small Round Lock	2	Pcs	H=25 mm
Bottom and roof cable entry	4	Nos	-----
Bottom air flow or cable entry	5	Nos	-----
Grounding cables	5	Pcs	Copper wire
Castor wheel with stopper	4	Pcs	--
L Rail	4	Pcs	SPCC T= 1.50 mm

Configuration Example

FS	B	42	-	6	1	D
Floor Standing Cabinet	Colour	Cabinet Height	Separator	Cabinet Width	Cabinet Depth	Front & Rear Door

FS	B	42	-	6	1	D
----	---	----	---	---	---	---

FS	Floor Standing Cabinet (Flat Pack) 1763 lbs (800kg)
----	---



B	RAL9004(Black)
G	RAL7044(Gray)
L	RAL7035(Light Gray)

18	18U/904
22	22U/1081
27	27U/1303
32	32U/1525
37	37U/1748
42	42U/1970
47	47U/2192

-	-
6	600
8	800

6	600
8	800
1	1000
12	1200

D	Front Glass and Rear Split Door
S	Front Glass and Rear Single Door
P	Front Perforated and Rear Split Door
R	Front Perforated and Rear Single Door
X	Front Door N/A
	Back Door N/A
	Side Panels N/A
V	Front Door Yes
	Back Door Yes
	Side Panels N/A



Ordering Information Examples

Part Code	Description
FSB22-81D	Cabinet, 22U FS 4xfans, wheels, FD Glass and Rear Honey Comb Double Doors,800x1000, Black

Compliance with regulations and certifications

