

Product datasheet

Specifications



Maintenance Bypass Panel, single unit, 20-60kW 400V wallmount, for Galaxy VS and Easy UPS 3S

GVSBPUSU20K60H

Overview

Presentation	Maintenance bypass panel for complete isolation of the UPS during service operations.
Lead time	Usually Ships within 2 Weeks

Main

Product or component type	Panel
Range of product	Galaxy VS
Range compatibility	Galaxy VS

Physical

Height	60 cm
Width	55 cm
Depth	22 cm
Net weight	25 kg

Environmental

Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-25...55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	46.000 cm
Package 1 Width	73.000 cm
Package 1 Length	80.000 cm
Package 1 Weight	43.000 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

How this information helps you >

Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

EU RoHS Directive

Compliant with Exemptions

SCIP Number

5aa5ed58-9f72-49f2-ad76-720ad4129c6e

REACH Regulation

[REACH Declaration](#)

China RoHS Regulation

[China RoHS declaration](#)

Energy efficiency

Optimized Energy Efficiency

Energy efficient product

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Take-back

Yes

Image of product / Alternate images

Alternative



